



Spec Sheet: 1-1/4" Adjustable Brass Impact Sprinkler (I125A)

Features

- Proven impact drive
- Rugged steel, bronze and stainless steel construction
- Stainless steel, tamper-resistant arc adjustment
- Adjustable from 20 to 340 degrees
- Anti-backsplash impact drive for reduced side splash
- Adjustable stainless steel pin for stream break-up
- Adjustable stainless steel deflector plate for distance control
- Stainless steel drive spring, trip assembly and drive pin
- Straight through flow, low pressure loss



Operating Range

- Pressure 50-100 PSI
- GPM 33-124
- Highest point of stream - 9ft. above nozzle level

Specifications

Nozzle	11/32" X 7/32"		3/8" X 7/32"		13/32" X 7/32"		7/16" X 7/32"		15/32" X 7/32"		1/2" X 1/4"	
	DIA	GPM	DIA	GPM	DIA	GPM	DIA	GPM	DIA	GPM	DIA	GPM
50	146	33	150	37	156	42	162	46	168	52	174	61
60	154	36	158	41	166	46	172	51	176	57	182	67
70	160	40	176	44	170	50	178	55	182	62	184	72
80	164	42	172	48	176	54	182	60	188	66	192	78
90	170	45	176	51	182	56	190	63	192	70	200	82
100	172	48	180	54	188	61	194	67	198	74	204	87

Nozzle	17/32" X 1/4"		9/16" X 1/4"		5/8" X 1/4"	
	DIA	GPM	DIA	GPM	DIA	GPM
50	180	66	188	73	194	86
60	188	72	194	80	202	94
70	196	78	202	87	208	103
80	202	84	208	93	214	110
90	208	90	212	99	220	117
100	212	94	218	105	224	124

