



# Spec Sheet:

## 3/4" Adjustable Brass Impact Sprinkler (I75A)

### Features

- Proven impact drive
- Rugged steel, bronze and stainless steel construction
- Stainless steel, tamper-resistant arc adjustment
- Adjustable from 20 to 340 degrees
- Anti-backsplash impact drive for reduced side splash
- Adjustable stainless steel pin for stream break-up
- Adjustable stainless steel deflector plate for distance control
- Stainless steel drive spring, trip assembly and drive pin
- Straight through flow, low pressure loss



### Operating Range

- Pressure 25-60 PSI
- GPM 3.8-14.00
- Spacing 42'-60'
- Highest point of stream—9ft. above nozzle level

### Specifications

Nozzle  PSI	3/16" x 3/32"		5/32" x 3/32"		11/64" x 3/32"	
	RADIUS	GPM	RADIUS	GPM	RADIUS	GPM
30	43	6.9	41	3.7	42	6
35	44	7.6	41	4.0	43	6.5
40	45	8.2	42	4.3	44	7
45	46	8.7	42	4.6	45	7.5
50	47	9.2	43	4.9	45	7.9
55	47	9.6	43	5.1	45	8.3
60	48	10.0	44	5.3	47	8.6



**WARNING:** This product can expose you to chemicals including Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)  
Wash hands after handling.